

DATASHEET

FUJITSU PRIMERGY RX100 S6 MONO SOCKET INTEL® XEON® RACK SERVER (1U)

COST OPTIMIZED AND HIGHLY MODULAR MULTI USAGE RACK SERVER

The PRIMERGY RX Rack Server family is the perfect platform to form dynamic infrastructures for your business processes today and in the coming decade. You will thus benefit several times over from our recognized experience in optimized data center technology and our innovative strength in developing energy-efficient and cost/performance-optimized rack systems for universal use. PRIMERGY rack servers, built upon industry standards, focus from a functional viewpoint on core features: energy efficiency, reliability, optimized for virtualization, ease of operation and maintenance, flexibility for your future. And thus they notably meet your requirements for outstanding cost efficiency. Optimal operating costs and long-term usability comply with the IT quality required by your customers. Our responsibility goes way beyond the hardware as our tailor-made service packages mean that you can rely on the best support for your IT during its whole lifecycle.

PRIMERGY RX100 S6

Data centers are increasingly seeking platform solutions that have minimal impact on their budgets and are easy to implement and run. PRIMERGY RX100 S6 is the right answer. The RX100 S6 meets the needs of business applications with its technical developments, such as Quad-Core Intel® Xeon® processor 3400 series and the new Dual-Core Intel® Core™ i3 processor, integrated RAID 0/1/5/6 and a memory of up to 32 GB. It unites the advantages of low-cost SATA or SAS/SSD hard disk technology with a space-saving 1U chassis and a depth of less than 60 cm. Integrated network and management functions together with the latest power saving technologies make the system ideal for infrastructure solutions for customers with limited budgets.



FEATURES AND BENEFITS

MAIN FEATURES	BENEFITS
<p>FLEXIBILITY</p> <ul style="list-style-type: none"> ■ 2x 3.5" SATA or SAS HDDs or 4x 2.5" SATA/SAS/SSD HDDs, all hot-plug with modular RAID controllers from low-entry embedded SATA RAID 0, 1; entry SAS 1.0 RAID 0, 1; newest SAS 2.0 RAID 0, 1 to performant SAS 2.0 RAID 5,6 controller <p>NEW PLATFORM</p> <ul style="list-style-type: none"> ■ Quad-Core Intel® Xeon® processor 3400 series with virtualization technology, and the new Intel® Core™ i3 processor series generation of Intel® Dual-Core CPUs with very low power consumption ■ Up to 32 GB of RAM - new dimensions for the mono socket server <p>ENERGY EFFICIENCY</p> <ul style="list-style-type: none"> ■ Low voltage Intel® Xeon® processors and new enhanced power supply with CSCI Silver certification and improved system energy features powered by iRMC S2 <p>RELIABILITY</p> <ul style="list-style-type: none"> ■ 2 x Gbit/s Ethernet LAN with TCP/IP accelerator plus switchable Service LAN (dedicated or shared) <p>SERVICEABILITY</p> <ul style="list-style-type: none"> ■ Customer Self Service Module or front VGA + USB 2.0 as option ■ System ID card with complete system information, e.g. Model, Serial Number, MAC Adresses etc. 	<ul style="list-style-type: none"> ■ Highly modular platform for all purposes that can be tailored exactly to customer requirements ■ More tasks are handled in less time. More efficient work is possible in your IT sector and less power consumption too. Quad-Core Xeon® provides significant performance/watt growth ■ Enough memory even for databases or virtualization tasks ■ Get the best performance but save energy and protect the environment ■ Top-speed communications link via LAN as standard ensures continuity in failover mode ■ Better serviceability and accessibility for low-entry rack environments ■ Have all the systems important informations handy in a second

TECHNICAL DETAILS

PRIMERGY RX100 S6

Housing type	Rack	Rack
Hard disk architecture	3.5" SAS/SATA	2.5" SAS/SATA

MAINBOARD

Mainboard type	D 2863
Chipset	Intel® 3420

PROCESSOR

Intel® Celeron® processor G1101 (2C, 2.26 GHz, SLC: , TLC: 2 MB, Turbo: No, 1066 MHz, 73 W)
Intel® Core™ i3 processor i3-530 (2C/4T, 2.93 GHz, SLC: , TLC: 4 MB, Turbo: No, 1333 MHz, 73 W)
Intel® Core™ i3 processor i3-540 (2C/4T, 3.06 GHz, SLC: , TLC: 4 MB, Turbo: No, 1333 MHz, 73 W)
Intel® Pentium® processor G6950 (2C, 2.80 GHz, SLC: , TLC: 3 MB, Turbo: No, 1066 MHz, 73 W)
Intel® Xeon® processor L3426 (4C/8T, 1.86 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 2/2/9/10, 1333 MHz, 45 W)
Intel® Xeon® processor X3430 (4C/4T, 2.40 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/2/3, 1333 MHz, 95 W)
Intel® Xeon® processor X3440 (4C/8T, 2.53 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/2/3, 1333 MHz, 95 W)
Intel® Xeon® processor X3450 (4C/8T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/4/4, 1333 MHz, 95 W)
Intel® Xeon® processor X3460 (4C/8T, 2.80 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/4/5, 1333 MHz, 95 W)
Intel® Xeon® processor X3470 (4C/8T, 2.93 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 2/2/4/5, 1333 MHz, 95 W)

Memory slots	4 (2 banks with 2 DIMMs each)
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	1 GB - 32 GB
Memory protection	Advanced ECC
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.

MEMORY OPTIONS

8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
1 GB (1 module(s) 1 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM

Memory modules notes	Unbuffered / Registered
-----------------------------	-------------------------

INTERFACES

USB ports	8 x (2x (+1x optional) front, 4x back, 1x internal planned for VMWare)
Graphics (15-pin)	1 x VGA (15-pin)
Serial connection	1 x serial RS-232-C, usable for iRMC or system or shared
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port

ONBOARD OR INTEGRATED CONTROLLER

SATA Controller type notes	SATA (for 1x DVD-RW / Blu-ray)
LAN Controller	Intel® 82574 + Intel® 82578 onboard, 2 x 10/100/1000 Mbit/s Ethernet (TCP/IP acceleration), PXE-Boot via LAN from PXE server, iSCSI Boot (also diskless) via onboard LAN

ONBOARD OR INTEGRATED CONTROLLER

Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	optional TPM

ONBOARD OR INTEGRATED CONTROLLER (BASE UNIT SPECIFIC)

RAID Controller	4 port SATA with RAID 0/1for HDD's	4 port SATA with RAID 0/1for HDD's
SATA Controller	4-port SATA 3Gb with RAID 0, 1	4-port SATA 3Gb with RAID 0, 1
SATA Controller type notes	for hot-plug SATA hard disks	for hot-plug SATA hard disks

SLOTS

PCI-Express 2.0 x4 (mech. x8)	1 x (for Modular RAID only)
PCI-Express 2.0 x8	2 x low profile (one of these can be used as standard short, 175mm)

DRIVE BAYS

Accessible drive bays	1 x 5.25/0.5-inch for CD-RW/DVD 1 x 3.5/0.5-inch for ServerView Local Service Panel or front VGA + USB 2.0
------------------------------	---

DRIVE BAYS (BASE UNIT SPECIFIC)

Hard disk bays	2 x 3.5-inch hot-plug SAS/SATA	4 x 2.5-inch hot-plug SAS/SATA
-----------------------	--------------------------------	--------------------------------

OPERATING PANEL

Operating buttons	On/off switch NMI button
Status LEDs	System status (amber / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (amber / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Panel (LSP)

BIOS

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
----------------------	--

SUPPORTED OPERATING SYSTEMS

Supported operating systems	Microsoft® Windows Server® 2008 R2 Microsoft® Windows Server® 2008 Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux Note: Support of other Linux derivatives on demand
Operating system release link	http://ts.fujitsu.com/software http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421

SERVER MANAGEMENT

Standard	ASR&R Automatic Server Recovery and Restart PDA Prefailure Detection and Analysis
Option	ServerView Integration for Tivoli TEC®, Tivoli NetView, HP NNM and HP Operations Manager iRMC S2 Advanced Pack
Server Management notes	Regarding Operating System dependencies for ServerView Suite Software Products see dedicated Product Data sheets.

DIMENSIONS / WEIGHT

Rack (W x D x H)	430 x 560 x 42.5 mm
Mounting Depth Rack	575 mm

DIMENSIONS / WEIGHT

Height Unit Rack	1 U
Mounting Cable depth rack	200 mm cable depth
Weight	up to 14 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

Floor-stand (W x D x H)

Rack (W x D x H)

ENVIRONMENTAL

Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	w/o PCIe cards 27.6 dB(A) (idle)/27.6 dB(A) (op.) / w/ PCIe cards 35.8 dB(A) (idle)/40.7 dB(A) (op.)
Sound power (LWAd; 1B = 10dB)	System w/o PCIe cards 4.4 B (idle)/4.3 B (operating) / w/ PCIe cards 5.2 B (idle)/ 5.7 B (operating)
Operating ambient temperature	15 - 35°C
Operating relative humidity	10 - 85 % (non condensing)

ELECTRICAL VALUES

Power supply configuration	1x standard power supply
Standard power supply output	350 W
Rated voltage range	100 - 127 V / 200 - 240 V
Rated frequency range	50 - 60 Hz
Rated current max.	6 A
Active power max. (per system unit)	288 W
Apparent power max. (per system unit)	293 VA
Heat emission	1036.8 kJ/h (982.9 BTU)

COMPLIANCE

Germany	GS
Europe	CE
USA/Canada	CSAc/us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Japan	VCCI
China	CCC
Australia/New Zealand	C-Tick
Taiwan	BSMI
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

COMPONENTS

HARD DISK DRIVES

SATA, 3 Gb/s, 750 GB, 7200 rpm, hot plug, 3.5-inch
 SATA, 3 Gb/s, 500 GB, 7200 rpm, hot plug, 3.5-inch
 SATA, 3 Gb/s, 250 GB, 7200 rpm, hot plug, 3.5-inch
 SATA, 3 Gb/s, 160 GB, 7200 rpm, hot plug, 3.5-inch
 SATA, 3 Gb/s, 1 TB, 7200 rpm, hot plug, 3.5-inch
 SAS, 6 Gb/s, 600 GB, 15000 rpm, hot plug, 3.5-inch
 SAS, 6 Gb/s, 450 GB, 15000 rpm, hot plug, 3.5-inch
 SAS, 6 Gb/s, 300 GB, 15000 rpm, hot plug, 3.5-inch
 SAS, 6 Gb/s, 300 GB, 10000 rpm, hot plug, 2.5-inch
 SAS, 6 Gb/s, 146 GB, 15000 rpm, hot plug, 2.5-inch
 SAS, 6 Gb/s, 146 GB, 10000 rpm, hot plug, 2.5-inch
 SAS, 6 Gb/s, 73 GB, 15000 rpm, hot plug, 2.5-inch
 SAS, 3 Gb/s, 146 GB, 15000 rpm, hot plug, 3.5-inch

Hard disk notes

One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
 Accessible capacity may vary, also depending on used software
 Mix of SAS and SATA HDD is possible but requires separate RAID sets and BC SATA drives

OPTICAL DRIVES

Blu-ray combo drive, (2x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
 DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I

SCSI / SAS CONTROLLER

SCSI Ctrl 320 MB 1x int /1x ext
 SAS Ctrl 3 Gb 4 ports int. / 4 ports ext.

RAID CONTROLLER

Integrated RAID 5/6 Ctrl, 6 Gb,
 RAID level: , 512 MB Cache, optional BBU (based on LSI SAS2108)
 Integrated RAID 0/1 Ctrl, SAS/SATA 3 Gb, 4 ports int.
 RAID level: 0, 1, 1E, no BBU support , for internal SAS tapes (based on LSI 1064e)

LAN CONTROLLER

Ethernet Ctrl 1 x 10 Gb Intel® Ethernet Server Adapter X520-DA2
 Ethernet Ctrl 1 x 1 Gb Intel® Gigabit CT Desktop Adapter
 Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PF Server Adapter
 Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PT Server Adapter
 Ethernet Ctrl 2 x 1 Gb Intel® PRO/1000 PT Dual Port Server Adapter
 Ethernet Ctrl 4 x 1 Gb Intel® PRO/1000 PT Quad Port Server Adapter
 SFP+ module 1 x 10 Gb Intel® Ethernet SFP+ Optics - LC SR

RACK INFRASTRUCTURE

Cable Arm 1U for PRIMECENTER- and 3rd-party racks
 Rackmount kit full extraction (760mm), tool less mounting
 Rackmount kit partly extraction (524mm), tool less mounting

WARRANTY

Standard Warranty 1 year
Service level On-site Service (depending on country)

MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION

Recommended Service 7x24, Onsite Response Time: 4h
Spare Parts availability 5 years

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu PRIMERGY RX100 S6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu PRIMERGY RX100 S6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://ts.fujitsu.com/Primergy>

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions
Mies-van-der-Rohe-Straße 8
80807 München
Germany
Website: www.ts.fujitsu.com
2010-02-02 CE-EN