

DATA SHEET

PRIMERGY RX300 S5

Issue: July 2009

Dual-Socket 2U Rack Server - Virtualization needs a reliable basis - RX300 S5 to meet the highest demands

The PRIMERGY RX Rack Server family is the perfect platform to form dynamic infrastructures for your business processes today and in the coming decade. You will thus benefit several times over from our recognized experience in optimized data center technology and our innovative strength in developing energy-efficient and cost/performance-optimized rack systems for universal use. PRIMERGY rack servers, built upon industry standards, focus from a functional viewpoint on core features: energy efficiency, reliability, optimized for virtualization, ease of operation and maintenance, flexibility for your future. And thus they notably meet your requirements for outstanding cost efficiency. Optimal operating costs and long-term usability comply with the IT quality required by your customers. Our responsibility goes way beyond the hardware as our tailor-made service packages mean that you can rely on the best support for your IT during its whole lifecycle.

PRIMERGY RX300 S5

The consolidation of dedicated servers and the use of efficient virtualized run environments provide measurable benefits and new flexibility regarding IT operations management. Virtual servers can thus be moved to other servers during ongoing operations and enable maintenance work to the hardware platform without any operational interruption. Active virtual servers can be flexibly moved to systems with higher performance for operation during peak-load times. Test systems can be very easily converted via live migration to production systems. Virtualized environments are the top application for RX300 systems and their new multicore CPUs in the Intel® Xeon® 5500 series. In this situation, several operating systems plus the installed applications have to run simultaneously on one and the same physical hardware. RX300 S5 provides all the platform features required for efficient virtualization:

- High, scalable I/O performances with PCIe Gen2, x4/x8 Turbo mode, up to 7 free PCIe slots - so that disk I/O and network/SAN accesses do not become a bottleneck!
- The generosity of the maximum 144 GB main memory for a high-performance determinable, optimal sizing of the virtual server environment so that the main memory does not become the point of contention for the virtualization software as well as the consolidated applications and the operating systems.
- Top performance with state-of-the-art Dual Quad or Turbo Quad-Core Intel® Xeon® 5500 series CPUs as well as double I/O performance with PCIe Gen2.0 - so that every virtual system can work at a higher performance level than before.
- The reliability of a premium server system in a space-saving 2 U design so that the cost benefits arising from standardized rack servers and virtual systems do not become a survival risk! The reliability of the RX300 server platform also leaves nothing to be desired in other application areas, e.g. as database servers or application servers for business-critical processes.



MAIN FEATURES	BENEFITS
<p>Dual, Quad and Turbo Quad-Core Intel Xeon 5500 series and 8 MB SLC</p> <p>Up to 144 GB state-of-the-art DDR3 main memory</p> <p>7 PCIe Gen2 double I/O throughput</p> <p>2 x Gbit/s Ethernet LAN with TCP/IP accelerator</p> <p>Patented IOOP (auto-accumulated 2x x4 to 1x x8)</p> <p>Choose between up to 12x2.5 or 6x3.5 inch hot-plug SAS and SATA hard disks</p> <p>Certification for Hyper-V, VMware, Xen Hypervisor</p>	<p>More virtual machines and applications can be used on one server</p> <p>More certainty that VMs run at high performance</p> <p>Double I/O bandwidth so that the combined SAN and network accesses achieve optimal throughput</p> <p>Low-priced high-speed slot option</p> <p>More than 3 TByte of low-priced internal hard disk memory</p> <p>Problem-free usage for market-relevant virtualization solutions</p>
<p>Memory sparing and memory mirroring option</p> <p>Hot-plug redundant power supply and fan,</p> <p>Hot-plug hard disks</p> <p>Cool-safe system design with high air throughput</p> <p>Integrated iRMC S2 Advanced Pack, integrated Remote Management Controller</p> <p>Module RAID for levels 0, 1, 5, 6.....</p> <p>Tailor-made service packages</p>	<p>Particularly high levels of availability and reliability</p> <p>Security level for each application scenario</p> <p>Permanently high performance levels available, increased component lifespan, less heat</p> <p>Easy, fast access from anywhere ensuring reliable operations</p> <p>Low-priced, powerful data security</p>
<p>Highly efficient power supply units ≥ 89 and 92% (EPA-compliant)</p> <p>Sensor-controlled fan management</p> <p>Power consumption management</p> <p>2.5 inch hard disks with low consumption</p> <p>Large slowly-rotating fans</p>	<p>Energy-efficient operation reduces the cooling system workload in the data center and saves money</p> <p>Individually defined profiles for power consumption</p> <p>Low noise levels and perfect heat dissipation</p>
<p>ServerView Local Service Panel (LSP) or display (LSD)</p> <p>Switchable service LAN (shared or dedicated)</p> <p>Illuminated green controls for hot-plug components</p> <p>Fully-extendable telescopic rails</p>	<p>Cost-reducing and pro-active customer self-service</p> <p>Physically separated service access</p> <p>Easy-to-use with standardized labelling</p> <p>Comfortable rack installation and server operation</p>
<p>ServerView Suite - Proven tools for the efficient management of physical and virtual resources throughout the entire lifecycle: perfect installation - stable operations – secure updates - exact (remote) maintenance – easy integration in specific corporate management solutions</p>	<p>The key to high-level IT benefits and reduced operational and service costs: greater reliability, lower downtimes and improved service quality</p>



Technical details

PRIMERGY RX300 S5

Housing type	Rack	Rack	Rack
Hard disk architecture	12x 2.5" SAS/SATA	6x 3.5" SAS/SATA	8x 2.5" SAS/SATA

Mainboard

Mainboard type	D 2619
Chipset	Intel® 5520
Processor quantity and type	1 - 2 x Intel® Xeon® processor 5500 series

Processor options

	Intel® Xeon® E5502 (2C, 1.86 GHz, SLC: 2 x 256 KB , TLC: 4 MB , Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)
	Intel® Xeon® E5504 (4C, 2.00 GHz, SLC: 4 x 256 KB , TLC: 4 MB , Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)
	Intel® Xeon® E5506 (4C, 2.13 GHz, SLC: 4 x 256 KB , TLC: 4 MB , Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)
	Intel® Xeon® E5520 (4C, 2.26 GHz, SLC: 4 x 256 KB , TLC: 8 MB , Turbo: Yes, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)
	Intel® Xeon® E5530 (4C, 2.40 GHz, SLC: 4 x 256 KB , TLC: 8 MB , Turbo: Yes, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)
	Intel® Xeon® E5540 (4C, 2.53 GHz, SLC: 4 x 256 KB , TLC: 8 MB , Turbo: Yes, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)
	Intel® Xeon® L5506 (4C, 2.13 GHz, SLC: 4 x 256 KB , TLC: 4 MB , Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 60 W)
	Intel® Xeon® L5520 (4C, 2.26 GHz, SLC: 4 x 256 KB , TLC: 8 MB , Turbo: Yes, 5.86 GT/s, Mem bus: 1066 MHz, 60 W)
	Intel® Xeon® X5550 (4C, 2.66 GHz, SLC: 4 x 256 KB , TLC: 8 MB , Turbo: Yes, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
	Intel® Xeon® X5560 (4C, 2.80 GHz, SLC: 4 x 256 KB , TLC: 8 MB , Turbo: Yes, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
	Intel® Xeon® X5570 (4C, 2.93 GHz, SLC: 4 x 256 KB , TLC: 8 MB , Turbo: Yes, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
Memory slots	18 (9 DIMMs per CPU, 3 channels with 3 slots per channel)
Memory slot type	DIMM (DDR3) registered
Memory capacity (min. - max.)	2 GB - 144 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Hot-spare memory support Memory Mirroring support
Memory notes	max. 144 GB registered; min. 2 GB registered; Memory Mirroring with 2 identical modules, Hot-spare Memory with three identical modules per channel
Memory Modules Independent Mode	2 GB (1 module(s) with 2 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500 2 GB (1 module(s) with 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600 4 GB (1 module(s) with 4 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500 4 GB (1 module(s) with 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600 8 GB (1 module(s) with 8 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500 8 GB (1 module(s) with 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600
Memory Modules Mirrored Mode	4 GB (2 module(s) with 2 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500 4 GB (2 module(s) with 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600 8 GB (2 module(s) with 4 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500 8 GB (2 module(s) with 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600 16 GB (2 module(s) with 8 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500 16 GB (2 module(s) with 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600

Memory Modules Performance Mode	6 GB (3 module(s) with 2 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500
	6 GB (3 module(s) with 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600
	12 GB (3 module(s) with 4 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500
	12 GB (3 module(s) with 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600
	24 GB (3 module(s) with 8 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500
	24 GB (3 module(s) with 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600

Interfaces

USB ports	10 x USB 2.0 (3x front, 4x rear, 2x internal for backup devices plus 1x USB stick)
Graphics (15-pin)	2 x VGA (thereof 1x front optional)
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC or system or shared
Serial 2 (9-pin)	1 x serial RS-232-C
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port

Onboard or integrated Controller

RAID Controller	Integrated RAID 0/1 or RAID 5/6 controller for SAS base units (occupies one PCIe slot, if at least 1 HDD is configured). See under Components RAID controller
SATA Controller	ICH10B, with two SATA channels for DVD + backup
LAN Controller	Intel® 82575EB, 2 x 10/100/1000 Mbit/s Ethernet (I/O acceleration), PXE Boot or iSCSI boot via onboard LAN
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)

Slots

PCI-Express Gen2 x4	5 x low profile
PCI-Express Gen2 x8	2 x low profile, both are notched x8 slot as well for x16 cards
Slot Notes	Two of four PCI-Express Gen2 x4 slots can be used as x8, if neighbour slot is empty. One PCIe Gen2 x4 slot may be occupied with a modular RAID controller if configured.

Drive bays

Hard disk bay configuration	6x 3.5-inch, for SAS / SATA or 8 or 12x 2.5-inch for SAS optional
Accessible drive bays	1 x 5.25/0.5-inch for CD-RW/DVD 1 x 3.5/0.5-inch for ServerView Local Service Panel or Local Service Display 1 x 3.5/1.6-inch for backup devices (occupies 2x 3.5-inch HDD for basic unit 6x 3.5-inch)
Notes accessible drives	All possible options described in relevant system configurator.

General system information

Number of fans	5
Fan configuration	Hot-plug

Operating panel

Operating buttons	On/off switch NMI button Reset button
Status LEDs	System status (amber / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (amber / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Panel (LSP) ServerView Local Service Display (LSD)

BIOS

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
---------------	--

Operating system

Supported operating systems	Microsoft® Windows Server® 2008 Microsoft® Windows Server® 2003 Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux Citrix® XenServer™ VMware Infrastructure Note: Support of other Linux derivatives on demand
Operating system release link	http://ts.fujitsu.com/software http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421

Server Management

Standard	ASR&R PDA
Option	ServerView Deployment Manager (fully functional unlimited version) ServerView Remote Management ServerView Integration for Tivoli TEC®, Tivoli NetView, HP OpenView NNM and HP OpenView iRMC S2 Advanced Pack
Server Management notes	Regarding Operating System dependencies for ServerView Suite Software Products see dedicated Product Data sheets.

Dimensions / Weight

Rack (W x D x H)	482.6 x 770 x 85.9 mm
Mounting Depth Rack	730 mm
Height Unit Rack	2 U
19" rackmount	Yes
Weight	up to 25 kg
Weight notes	Weight may vary depending on actual configuration
Rack integration kit	Rack integration kit as option

Floor-stand (W x D x H)

Rack (W x D x H)

Environmental

Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	45 dB(A) (idle) / 45 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	6.2 B (idle) / 6.2 B (operating)
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)

Electrical values

Power supply configuration	hot-plug power supply as standard, redundancy as option (1 + 1 redundancy)
Max. output of power supply	800 W
Hot-plug power supply redundancy	Yes
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Rated current max.	8.0 A – 3.5 A (100 V / 240 V)
Rated current in basic configuration	4.2 A - 1.4 A (100 V / 240 V)
Active power max. (per system unit)	733 W
Apparent power max. (per system unit)	737 VA
Heat emission	2638.8 kJ/h (2501.7 BTU)

Compliance	
Germany	GS
Europe	CE
USA/Canada	CSAc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Japan	VCCI
Australia/New Zealand	C-Tick
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Components

Hard disk drives	
	SATA, 120 GB, 5400 rpm, hot plug, 2.5-inch
	SATA, 3 Gb/s, 750 GB, 7200 rpm, hot plug, 3.5-inch
	SATA, 3 Gb/s, 500 GB, 7200 rpm, hot plug, 3.5-inch
	SATA, 3 Gb/s, 250 GB, 7200 rpm, hot plug, 3.5-inch
	SATA, 3 Gb/s, 1 TB, 7200 rpm, hot plug, 3.5-inch
	SAS, 3 Gb/s, 450 GB, 15000 rpm, hot plug, 3.5-inch
	SAS, 3 Gb/s, 300 GB, 15000 rpm, hot plug, 3.5-inch
	SAS, 3 Gb/s, 300 GB, 10000 rpm, hot plug, 2.5-inch
	SAS, 3 Gb/s, 146 GB, 15000 rpm, hot plug, 3.5-inch
	SAS, 3 Gb/s, 146 GB, 10000 rpm, hot plug, 2.5-inch
	SAS, 3 Gb/s, 73 GB, 15000 rpm, hot plug, 3.5-inch
	SAS, 3 Gb/s, 73 GB, 15000 rpm, hot plug, 2.5-inch
	SAS, 3 Gb/s, 73 GB, 10000 rpm, hot plug, 2.5-inch
	SAS, 3 Gb/s, 36 GB, 15000 rpm, hot plug, 2.5-inch

Hard disk notes	Mix of 3.5-inch SAS and SATA HDD is possible but requires separate RAID sets One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software
-----------------	---

Tape Drives	
	DDS Gen5 (for 3.5-inch HDD bay), 36 GB , 3 MB/s, half height, USB 2.0
	DDS Gen5 3.5", 36 GB , 3 MB/s, half height, USB 2.0
	RDX Drive (for 3.5-inch HDD bay), 80 GB, 160 GB, 320 GB , 25 MB/s, half height, USB 2.0
	RDX Drive 3.5", 80 GB, 160 GB, 320 GB , 25 MB/s, half height, USB 2.0

Optical drives	
	Blu-ray combo drive, (2x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I

SCSI / SAS Controller	
	SCSI Ctrl 320 MB 1x int /1x ext
	SAS Ctrl 3 Gb 4 ports int. / 4 ports ext.

RAID Controller	
	RAID 5/6 Ctrl, SAS/SATA 3 Gb, LSI MegaRAID SAS8880E, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI 1078)
	Integrated RAID 5/6 Ctrl, SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI 1078)
	Integrated RAID 5/6 Ctrl, SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 256 MB Cache, optional BBU (based on LSI 1078)
	Integrated RAID 0/1 Ctrl, SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 1E, no BBU support (based on LSI 1068e)

Fibre Channel controller	
	Fibre Channel Ctrl 2 x 4 Gb Emulex LPe11002 MMF LC
	Fibre Channel Ctrl 1 x 4 Gb Emulex LPe1150 MMF LC
	Fibre Channel Ctrl 1 x 4 Gb Qlogic QLE2460 MMF LC
	Fibre Channel Ctrl 2 x 4 Gb Qlogic QLE2462 MMF LC
	Fibre Channel Ctrl 2 x 8 Gb Emulex LPe12002 MMF LC
	Fibre Channel Ctrl 1 x 8 Gb Emulex LPe1250 MMF LC

LAN Controller	Ethernet Ctrl 1 x 1 Gb Intel® Gigabit CT Desktop Adapter
	Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PF Server Adapter
	Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PT Server Adapter
	Ethernet Ctrl 2 x 10 Gb Intel® 10 Gigabit XF SR Dual Port Server Adapter
	Ethernet Ctrl 2 x 1 Gb Intel® PRO/1000 PT Dual Port Server Adapter
	Ethernet Ctrl 4 x 1 Gb Intel® PRO/1000 PT Quad Port Server Adapter

LAN Controller notes	Ethernet Ctrl 1 x 1 Gb Intel® Gigabit CT Desktop Adapter requires RHEL 4.8 or higher
----------------------	--

Rack infrastructure	Cable Arm 2U for 3rd party racks
	Cable Management for 19-inch DataCenter / PRIMECENTER Racks
	Rackmount kit full extraction (760mm), tool less mounting
	Rackmount kit partly extraction (524mm), tool less mounting

Warranty	
Standard Warranty	3 years
Service level	On-site Service
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:

<http://ts.fujitsu.com/aboutus>

Take back and Recycling information:

<http://ts.fujitsu.com/recycling>

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
 Copyright © Fujitsu Technology Solutions July 2009

Published by
 Fujitsu Technology Solutions
<http://ts.fujitsu.com>