

DATASHEET

FUJITSU PRIMERGY TX150 S7 MONO-SOCKET INTEL® XEON® PROCESSOR SERVER

THE ONE-PROCESSOR TOWER SERVER - MAXIMIZED!

PRIMERGY TX industry standard tower servers: efficient, rock solid, record-breaking performance. PRIMERGY TX servers benefit from over 20 years pioneering work in the field of Green IT. That is how TX servers reach industry – leading performance per watt ratios, lowering the environmental impact and running costs. TX servers can easily be managed locally or remotely via the PRIMERGY ServerView Suite, saving IT admin costs. That's efficient performance. Our made-to-measure service packages take care of your system every step of the way. Rest assured, PRIMERGY TX servers are put through 5000 boot cycles - that's rock solid performance. PRIMERGY TX servers are flexible systems capable of using up to two processors and up to 20 hard disks. Tower to rack mounting kits are available for most TX systems to help you move to a consolidated rack infrastructure. TX servers have a tradition of setting record-breaking performance levels. So, whether you use them as tower or rack servers, for file, print or application purposes, you will benefit from record-breaking performance. PRIMERGY TX: a tower of strength.

PRIMERGY TX150 S7

The PRIMERGY TX150 S7: the right system for SMEs or non-mission-critical decentralized infrastructures where the main focus is on expandability and availability. The expandability and availability come from the 6 expansion slots (5 of which PCIe Gen 2) and up to 8x 2.5" hot-plug hard disks. Increase the system's availability and energy efficiency through the use of optional redundant power supplies boasting up to 89% energy efficiency. The TX150 S7 also offers up to the latest generation Intel® Xeon® processor 3400 series single processor platform, delivering excellent energy-efficient performance at an attractive price. The PRIMERGY TX150 S7: the one processor tower server – maximized!



FEATURES AND BENEFITS

MAIN FEATURES	BENEFITS
<ul style="list-style-type: none">■ By combining the latest Intel® mono-processor platform and SAS 2.0 hard disks with Fujitsu's engineering, you can get great performance with low energy consumption.■ Hot plug hard disks: choose between max. 4x 3.5 or max. 8x 2.5". Power supply units: choose between standard or redundant.■ Up to 32GB of RAM and 6 expansion slots (5 of which second generation PCIe slots)■ The PRIMERGY TX150 S7 can be integrated into a rack infrastructure with the tower to rack conversion kit■ The green touch points, the system ID card and the customer self-service module make servicing the TX150 S7 easier	<ul style="list-style-type: none">■ High performance and energy efficiency■ High availability options to suit your business■ High expandability - the TX150 S7 grows with your business.■ High versatility - increases your investment's lifetime■ High serviceability - saves your time

TECHNICAL DETAILS

MAINBOARD

Mainboard type	D 2759
Chipset	Intel® 3420

PROCESSOR

Intel® Celeron® processor G1101 (2C, 2.26 GHz, SLC: , TLC: 2 MB, Turbo: No, 1066 MHz, 73 W)
Intel® Core™ i3 processor i3-530 (2C/4T, 2.93 GHz, SLC: , TLC: 4 MB, Turbo: No, 1333 MHz, 73 W)
Intel® Core™ i3 processor i3-540 (2C/4T, 3.06 GHz, SLC: , TLC: 4 MB, Turbo: No, 1333 MHz, 73 W)
Intel® Pentium® processor G6950 (2C, 2.80 GHz, SLC: , TLC: 3 MB, Turbo: No, 1066 MHz, 73 W)
Intel® Xeon® processor L3426 (4C/8T, 1.86 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 2/2/9/10, 1333 MHz, 45 W)
Intel® Xeon® processor X3430 (4C/4T, 2.40 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/2/3, 1333 MHz, 95 W)
Intel® Xeon® processor X3440 (4C/8T, 2.53 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/2/3, 1333 MHz, 95 W)
Intel® Xeon® processor X3450 (4C/8T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/4/4, 1333 MHz, 95 W)
Intel® Xeon® processor X3460 (4C/8T, 2.80 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 1/1/4/5, 1333 MHz, 95 W)
Intel® Xeon® processor X3470 (4C/8T, 2.93 GHz, SLC: 4 x 256 KB, TLC: 8 MB, Turbo: 2/2/4/5, 1333 MHz, 95 W)

Memory slots	6
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	1 GB - 32 GB
Memory protection	ECC
Memory notes	4GB with 1066MHz or 8GB RDIMM and all UDIMM modules: 4 DIMMs max; with 2 channels and 2 slots per channel. UDIMMs (max. 16MB) with all processors; RDIMMs (max. 32 GB) for Xeon CPUs only

MEMORY OPTIONS

8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
1 GB (1 module(s) 1 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM

Memory modules notes	1066 MHz and 1333 MHz memory modules cannot be mixed
-----------------------------	--

INTERFACES

USB ports	10 x USB 2.0 (3x front, 4x rear, 3x internal)
Graphics (15-pin)	1 x VGA
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC or system or shared
Serial 2 (9-pin)	1 x serial RS-232-C (optional)
LAN / Ethernet (RJ-45)	1 x Gbit/s Ethernet
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port

ONBOARD OR INTEGRATED CONTROLLER

RAID Controller	Integrated RAID 0/1 or RAID 5/6 controller for SAS base units (option, occupies one PCIe slot). See under Components RAID controller
SATA Controller	Intel® 3420 Ixex Peak PCH Platform Control Hub, 2 ports used for accessible drives 4 port for internal SATA HDDs with RAID 0, 1, 10 for Windows and Linux;
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / 1.2 (option)

SLOTS

PCI Express 2.0 x1 (mech. x4)	2 x
PCI-Express 2.0 x4 (mech. x8)	1 x Low profile ready, full height, long 3,3V
PCI-Express 2.0 x8	2 x short 3,3V
PCI slots	1 x PCI 32/33 MHz, 1x long, 5V

SLOTS	
Slot Notes	in SAS configuration 1x PCI-Express occupied by modular RAID controller
DRIVE BAYS	
Hard disk bay configuration	4x 3,5-inch, for SAS / SATA or 8x 2,5-inch for SAS/SATA/SSD optional
Accessible drive bays	3 x 5.25/1.6-inch
Notes accessible drives	all possible options described in relevant system configurator
Number of fans	1
Fan configuration	1 standard fan
OPERATING PANEL	
Operating buttons	On/off switch NMI button Reset button
Status LEDs	System status (amber / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (amber / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Panel (LSP) ServerView Local Service Display (LSD)
BIOS	
BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
SUPPORTED OPERATING SYSTEMS	
Supported operating systems	Microsoft® Windows Server® 2008 R2 Microsoft® Windows Server® 2008 Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux Note: Support of other Linux derivatives on demand
Operating system release link	http://ts.fujitsu.com/software http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421
SERVER MANAGEMENT	
Standard	ASR&R Automatic Server Recovery and Restart PDA Prefailure Detection and Analysis Online update packages for BIOS, firmware drivers and ServerView Agents ServerView Integration solutions for Microsoft SMS, MOM, SCOM, SCCM and Altiris Deployment Solution ServerView Deployment Manager (fully functional 30-day trial version) ServerView Deployment Manager (fully functional 30-day trial version)
Option	iRMC S2 Advanced Pack ServerView Integration for Tivoli TEC®, Tivoli NetView, HP NNM and HP Operations Manager
Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.
DIMENSIONS / WEIGHT	
Floor-stand (W x D x H)	205 x 584 x 444 mm
Rack (W x D x H)	482 x 570 x 220 mm
Dimension notes	Floorstand Width 306 mm with tilt protection; depth measured excludes handles on redundant PSU. Rack depth excludes handles of red PSU and rack front.

DIMENSIONS / WEIGHT

Height Unit Rack	5 U
Weight	21-28 Kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

DIMENSIONS / WEIGHT / ENVIRONMENTAL (BASE UNIT SPECIFIC)

Floor-stand (W x D x H)	
Rack (W x D x H)	

ENVIRONMENTAL

Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	SATA: 24 dB(A) idle mode/ 25 dB(A) operation mode; SAS: 31 dB(A) idle mode/ 33 dB(A) operation mode
Sound power (LWAd; 1B = 10dB)	SATA: 4.2 B idle mode/ 4.2 B operation mode ; SAS: 4.9 B idle mode/ 5.1 B operation mode
Noise notes / description	May vary according to configuration
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)

ELECTRICAL VALUES

Power supply configuration	Base unit specific: 1x standard power supply or 1x hot-plug power supply or 2x hot plug power supply for redundancy
Standard power supply output	350W (85% efficiency)
Hot-plug power supply output	450W (89% efficiency)
Hot-plug power supply redundancy	Yes
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Rated current max.	6A - 3A The rated current in basic configuration values are pending confirmation.
Rated current in basic configuration	1.9 A - 0.8 A
Active power max. (per system unit)	258 W
Apparent power max. (per system unit)	81 VA - 258 VA (max. active power and max. apparent power values are configuration dependent) VA
Heat emission	928.8 kJ/h (880.5 BTU)

COMPLIANCE

Germany	TÜV GS
Europe	CE label according to EU directives: Low-Voltage Directive 2006/95/EC, Electromagnetic Compatibility 2004/108/EC EN 300386 EN 50371 EN 55022 EN 55024 EN 60950 - 1 EN 61000-3-2 JEIDA EN 61000-3-3
USA/Canada	CSAc/us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Japan	VCCI class A + JIS 61000-3-2
Russia	GOST-R
China	CCC (G 4943/ GB 9245 / GB 17625)
Australia/New Zealand	C-Tick (AS / NZS CISPR 22 Class A)
Taiwan	BSMI class A (CNS 13438, CNS 14336) CNS 14336

COMPLIANCE

Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. Additional compliance with: Kenya:KEBS; Kuwait: KUCAS; Nigeria:SONCap; South Africa:SABS; Belarus: STB; Kazakhstan: GOST-K; Ukraine: SEMPRO
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

COMPONENTS

HARD DISK DRIVES

SATA, 3 Gb/s, 750 GB, 7200 rpm, hot plug, 3.5-inch
SATA, 3 Gb/s, 500 GB, 7200 rpm, hot plug, 3.5-inch
SATA, 3 Gb/s, 320 GB, 5400 rpm, hot plug, 2.5-inch
SATA, 3 Gb/s, 160 GB, 5400 rpm, hot plug, 2.5-inch
SATA, 3 Gb/s, 1 TB, 7200 rpm, hot plug, 3.5-inch
SAS, 6 Gb/s, 600 GB, 15000 rpm, hot plug, 3.5-inch
SAS, 6 Gb/s, 450 GB, 15000 rpm, hot plug, 3.5-inch
SAS, 6 Gb/s, 300 GB, 15000 rpm, hot plug, 3.5-inch
SAS, 6 Gb/s, 300 GB, 10000 rpm, hot plug, 2.5-inch
SAS, 6 Gb/s, 146 GB, 15000 rpm, hot plug, 2.5-inch
SAS, 6 Gb/s, 146 GB, 10000 rpm, hot plug, 2.5-inch
SAS, 6 Gb/s, 73 GB, 15000 rpm, hot plug, 2.5-inch
SAS, 3 Gb/s, 146 GB, 15000 rpm, hot plug, 3.5-inch

Hard disk notes

One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
Accessible capacity may vary, also depending on used software
No mix of SAS and SATA HDDs possible

TAPE DRIVES

DDS Gen5, 36 GB , 3 MB/s, half height, USB 2.0
DDS Gen6, 80 GB , 6 MB/s, half height, USB 2.0
LTO2HH Ultrium, 200 GB , 24 MB/s, half height, SAS 3Gb/s
LTO3HH Ultrium, 400 GB , 60 MB/s, half height, SAS 3Gb/s
LTO4HH Ultrium, 800 GB , 120 MB/s, half height, SAS 3Gb/s
RDX Drive, 80 GB, 160 GB, 320 GB , 25 MB/s, half height, USB 2.0

OPTICAL DRIVES

Blu-ray combo drive, (2x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
Blu-ray combo drive, (6x BD-ROM; 16x DVD; 40x CD), half height, SATA I
DVD-ROM, (16xDVD; 48xCD), half height, SATA I
DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I

SCSI / SAS CONTROLLER

SCSI Ctrl 320 MB 1ch int/ext PCIe x1
SAS Ctrl 3 Gb 4 ports int. / 4 ports ext. PCIe x4

RAID CONTROLLER

Integrated RAID 5/6 Ctrl, SAS 6 Gb, 8 ports int. RAID level: 0, 1, 1+0, 5, 5+0, 6, 6+0, 512 MB Cache, optional BBU (based on LSI SAS2108)
Integrated RAID 0/1 Ctrl, SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 1E, no BBU support (based on LSI 1068e)
Integrated RAID 0/1 Ctrl, SAS/SATA 3 Gb, 4 port int. RAID level: 0, 1, 1E, no BBU support , for internal SAS tapes (based on LSI 1064e)

LAN CONTROLLER

Ethernet Ctrl 1 x 1 Gb Intel® Gigabit CT Desktop Adapter
Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PF Server Adapter
Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PT Server Adapter
Ethernet Ctrl 2 x 1 Gb Intel® PRO/1000 PT Dual Port Server Adapter
Ethernet Ctrl 4 x 1 Gb Intel® PRO/1000 PT Quad Port Server Adapter

RACK INFRASTRUCTURE

Cable Arm 2U for 3rd party racks

Cable Management for 19-inch DataCenter / PRIMECENTER Racks

WARRANTY

Standard Warranty

1 year

Service level

On-site Service (depending on country)

MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION

Recommended Service

7x24, Onsite Response Time: 4h

Service Weblink

<http://ts.fujitsu.com/Supportservice>

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu PRIMERGY TX150 S7, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu PRIMERGY TX150 S7, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://ts.fujitsu.com/Primergy>

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment/>



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner